

AV 725 AV 725P AV 727P AV 728

NITRILE COATED SAFETY GLOVES USER INFORMATION

GLOVE DESCRIPTION

The gloves have a light Nitrile coating either on palm or fully coated. The inner liner is a 100% cotton interlock with either a cotton wristing, safety cuff or PVC cuff. The gloves are excellent for all round general handling situation. The gloves shall not be worn when there is a risk of entanglement with moving parts of machines.

GLOVE SERIES

AV725P Knitted Wrist Palm Coated.
AV725 Knitted Wrist Fully Coated.
AV727P Knitted Wrist Palm Coated.
AV728 Knitted Wrist Fully Coated.

MARKING

(U), STYLE, SIZE AND CE

GLOVE SIZES AVAILABLE	
Hand Size defined in EN 420	Glove Sizes
7	7
8	8
9	9
10	10
11	11

INTERMEDIATE

Safety Category



2111



Mechanical test data in accordance with EN388:2003

Abrasion	Resistance	Level 2
Cut	Resistance	Level 1
Tear	Resistance	Level 1
Puncture	Resistance	Level 1

Dexterity performance level is 5 in accordance with EN 420:2003.

The results are taken from the palm area of the gloves

All EC type examinations were carried out by

SGS United Kingdom Ltd. 202B Worle Parkway, Weston-super-Mare, BS22 6WA, UK. Notified Body No. 0120.
(Notified Body No. 0120)

CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected, especially after cleaning treatment, before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible, provided no serious hazards exist, before removal from hands. Excess contaminant should first be removed and the gloves may be decontaminated with mild detergent solution then rinsed with clean water and dried ideally with some air movement. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternately using the gloved hand so that the gloves are removed without the contaminant contacting bare hands.

STORAGE

Store the gloves in cool dry place and out of direct sun light.

OBSOLESCENCE

When stored properly, will not suffer changes in the mechanical properties from the date of manufacture. Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

GENERAL

These products are manufactured under a Quality System which has been registered and meets the requirements of ISO 9001.

The models referred to are designed to accommodate the basic safety requirements and standards laid down in EU Council Directive for Personal Protective Equipment Annex II and EN 420:2003, EN 388:2003 respectively.

None of the raw materials or processes used in the manufacture of these products are known to have any harmful effect on the wearer.

NOTE

Hand protection is limited to the Nitrile Rubber Coated area of the glove. The information contained herein is intended to assist the wearer in selection of Personal Protective Equipment. The results of the laboratory tests should also help in glove selection, however it must be understood that the actual conditions of use cannot be simulated. It is therefore the responsibility of the user and not the manufacturer to determine the glove suitability for the intended use.

Further information is available at the below address.

Ultimate Industrial Ltd.

Victoria House, Colliery Road, Horseley Fields,
Wolverhampton, WV1 2RD, UK