

**USER INFORMATION****ACEGRIP-LITE**  
Latex Coated Polyester Glove**GLOVE SERIES:** ACEGRIP-LITE**MARKING**    ,SIZE,**GENERAL**

These products are classed as Personal Protective Equipment (PPE) by the European PPE Directive 89/686/EEC and have been shown to comply with this Directive through the Harmonised European Standard BS EN 388, BS EN 420.

**FEATURES**

13 Gauge polyester glove with crinkle finish LATEX coated palm and fingertips. Gloves are designed for general handling. *Avoid using near moving machinery due to entanglement hazard.*

**AVAILABLE STYLES**

ACEGRIP-LITE – Fully coated face and part coated back (over finger tips), Black coating on red shell.

**AVAILABLE SIZES**

6,7, 8, 9, 10,11 All sizes comply with the EN420:2003 for comfort, fit and dexterity.

**STORAGE:** Gloves should be ideally stored in original packaging at ordinary temperatures and humidity in clean, covered and ventilated premises.

**CLEANING / MAINTENANCE**

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. Laundering of these gloves is not recommended.

**CAUTION**

These gloves have been tested to BS EN 388 and the protection referred to applies only to the palm area of the gloves. The result of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the gloves suitability for the intended use.

**OBSOLESCENCE**

When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

**EN 388:2003**

3 1 3 1

**Mechanical Risks**

Abrasion resistance	3
Blade cut resistance	1
Tear Resistance	3
Puncture Resistance	1

Test results are taken from the palm area of the gloves

These gloves meet the requirements of European PPE Directive 89/686/EEC for innocuousness, comfort, solidity.  
This glove meets the requirements of EN420, General Requirements for Work Gloves, Dexterity 5.

**Please Note:**

This glove contains NATURAL RUBBER LATEX which may cause an allergic reaction in some users. If affected discontinue use immediately and seek medical advice.

These Pictograms indicate that the product protects against:- **Mechanical Risks EN 388:2003.**  
The numbers indicate performance levels.

**PROTECTION LIMITS**

This glove is not liquid proof. Protection against risks or hazards not mentioned in this document is not warranted. The levels of performance mentioned are ONLY valid for new gloves. The glove should not be allowed to come into contact with fire. Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machinery.

Tested in accordance with EN 420:2003, EN 388: 2003. EC type examinations were carried out by  
CTC, 4 rue Herman Frenkel, 69367 LYON, Cedex 07, FRANCE (notified body 0075)

Further information may be obtained from the address below.

**ULTIMATE INDUSTRIAL**  
Victoria House, Colliery Road,  
Horseley Fields, Wolverhampton  
United Kingdom