



CAT II

USER INFORMATION

ICETHERM BLK

Coated Glove

GLOVE SERIES: ICETHERM BLK

MARKING



ICETHERM BLK, SIZE, AND



GENERAL

These products are classed as Personal Protective Equipment (PPE) by the European PPE Directive 89/686/EEC and have been shown to comply with this Directive through the Harmonised European Standard BS EN 388, BS EN 420, BS EN 511.

FEATURES

Foam PVC coated acrylic and nylon glove with part coated backing. These gloves are designed for use in cold conditions for general handling. The gloves offer protection against mechanical and cold risks. *Avoid using near moving machinery due to entanglement hazard.*

AVAILABLE STYLES

ICETHERM BLK- Fully coated face and part coated back (over knuckles)

AVAILABLE SIZES

7, 8, 9, 10, 11

STORAGE: Gloves should be ideally stored in dry conditions in original package, away from direct sunlight.

CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. Laundering of these gloves is not recommended. The performance characteristics of worn and laundered gloves may vary from those of new gloves (shown below).

CAUTION! *Avoid using near moving machinery due to entanglement hazard.*

These gloves have been tested to BS EN 388 and the protection referred to applies only to the palm area of the gloves when NEW. The result of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the gloves suitability for the intended use

OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

EN 388:2003



3 2 3 2

Mechanical Risks

Abrasion resistance (1-4)	3
Blade cut resistance (1-5)	2
Tear Resistance (1-4)	3
Puncture Resistance (1-4)	2

Test results are taken from the palm area of the gloves

EN 511:2006



0 2 0

Cold Risks

Convective cold (0-4)	0
Contact cold (0-4)	2
Water penetration (0-1)	0

The Pictograms above indicate that the product protects against:- **Mechanical Risks EN 388:2003 and Cold EN511:2006**
The numbers indicate performance levels.

PROTECTION LIMITS

Protection against risks or hazards not mentioned in this document is not warranted. The levels of performance mentioned are ONLY valid for new gloves. The glove should not be allowed to come into contact with fire. Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machinery.

Tested in accordance with EN 420:2003, EN 388: 2003, EN 511:2006. EC type examinations were carried out by SGS United Kingdom Limited, Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom.(NOTIFIED BODY 0120)

Further information may be obtained from the address below.

Ultimate Cleaners Industrial Ltd, Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK