




# CE CAT II

## USER INFORMATION

# KUTLASS LX500

GLOVE SERIES KUTLASS LX500

MARKING  Style, SIZE,  , & CE

### GLOVE SIZE AVAILABLE

HAND SIZE DEFINE IN EN 420:2063/A1:2009	GLOVE SIZE
6	XS/6
7	S/7
8	M/8
9	L/9
10	XL/10
11	XXL/11

### FEATURE

The gloves are machine knitted liners made from HPPE, Glass and other synthetic yarns with Natural Latex coating to provide a good cut resistance barrier, while offering flexibility and comfort. Store dry and cool. The glove provides good protection against abrasion and tear in dry handling conditions. Dexterity Level 5.

**NOTE:** These gloves are cut resistance not cut proof. Do not use near moving machines if there is a risk of entanglement.

**CAUTION!** This product contains natural rubber latex, which may cause serious allergic reaction in some individuals. Users with a known sensitivity to rubber or latex products should avoid contact. If you experience a reaction to this product, discontinue use and seek medical attention. Reaction may include such phenomenon as watery eyes, wheezing, hives, rash, welts, redness, dryness, tingling or other skin irritations, hay fever like symptoms such as sneezing, running nose, itching throat or nose or lightness of the chest.

### CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Do not use Chlorine bleaches.

**Note:** The performance characteristics of worn and laundered gloves may differ from the results shown below.

### OBsolescence

When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

### GENERAL

None of the materials or processes used in the manufacture of these products is known to be harmful to the wearer.

### PLEASE NOTE

The results of the physical tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use.

EN 388:2003



3 5 4 2

This Pictogram indicates that the product protects against Mechanical risks and complies under EN 388:2003. The numbers indicate performance levels.

- (INTERMEDIATE)
- Safety Category
- 3 Abrasion Resistance
- 5 Cut Resistance
- 4 Tear Resistance
- 2 Puncture Resistance

Test results are taken from the palm area of the gloves.

All EC type examinations were carried out by SATRA Technology Centre Ltd., Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom. (Notified Body No. 0321) in accordance with EU directive 89/686/EEC

Further information may be obtained from:

Ultimate Industrial Ltd,  
Victoria House, Colley Road,  
Wolveshampton, W1 2SD  
UK