

## PREMIER PLUS RIGGER 21543 (Yellow) ONE SIZE



Certification Body: SATRA Technology Centre, Kettering, NN16 8SD, UK Notified Body: 0321
These products are classed as Personal Protective Equipment by the European PPE Directive 89/686/EEC

## CAREFULLY READ INSTRUCTIONS BEFORE USE

This product is designed to provide protection against: Mechanical Risks and Contact Cold. No item of PPE can provide full protection - care must always be taken whilst carrying out the activity.

EN 420:2003+A1:2009 Protective Gloves - General Requirements

**Fitting & Sizing**: Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection.

Storage & Transport: Store the product in a well ventilated area away from extremes of temperature & strong odours.

Inspection Before & After Use: Discard and replace damage products before use. If in doubt consult manufacturer.

Cleaning: It is recommended that this product should not be washed or dry-cleaned.

EN 388:2003 Protective Gloves Against Mechanical Risks

Test	Level Achieved	Maximum Level
Abrasion Resistance	3	(4)
Blade Cut Resistance	2	(5)
Tear Resistance	3	(4)
Puncture Resistance	2	(4)

**Note**: Performance levels apply to the palm area of the hand.

Warning: These gloves will not prevent crushing injuries, or injuries associated with vibration. They are not to be worn when there is a risk of entanglement by moving parts of machinery. EN 388:2003



3232

EN 511:2006 Protective Gloves Against Cold

Property	Level Achieved	Maximum Level
Convective Cold	1	(4)
Contact Cold	2	(4)
Water Penetration	Х	(1)

Warning: The glove not reaching a level of performance of 1 according to water penetration test, may lose its insulative properties when wet.

Selection Process: The individual conditions, environment and occupation must be considered when selecting a

EN 511:2006



12X