

# EC Declaration of Product Conformity

The manufacturer established in the community;

**BM Polyco Ltd  
Crown Road  
Enfield  
EN1 1TX  
United Kingdom**

Certified to ISO 9001

declares that the new PPE described hereafter



## **VYFLEX & VYFLEX BOA** PVC Coated Gauntlets

is in conformity with the provisions of Council Directive 89/686/EEC and where such is the case, with National Standards transposing harmonised standards EN374-1:2003, EN374-2:2003, EN374-3:2003, EN388:2003 and EN420:2003.

is identical to the PPE which is the subject of EC certificate of conformity Nos. GB10/80669 and GB10/80668 issued by SGS United Kingdom Ltd, 202B Worle Parkway, Weston-super-Mare, BS22 6WA, UK (Notified Body No. 0120).

is subject to the procedure set out in Article 11B of Directive 89/686/EEC under the supervision of the Notified Body SGS (Notified Body No. 0120).

**MECHANICAL  
HAZARDS  
EN388**



**MICRO  
ORGANISM  
HAZARDS  
EN374**



**CHEMICAL  
HAZARDS  
EN374**



**JKL**

**PROTECTIVE  
GLOVES  
AGAINST COLD  
EN511**



**Vyflex BOA only**

<b>EN511 (Vyflex BOA only)</b>	<b>Performance Level</b>
Convective Cold	1
Contact Cold	2
Water Impermeability	1

EN388	Vyflex	Vyflex BOA
Abrasion	4	4
Blade cut	1	1
Tear	2	3
Puncture	1	1

**CE 0120**



Complex Design

### User Information

Glove care: To get the best service from your gloves ensure that after use all contaminant is removed.

Storage: store in dry conditions away from direct sunlight and heat.

You are advised to retain this packaging for reference.

Note: should not be worn where there is a risk of entanglement with moving machinery.

This data may not reflect actual duration of protection in the workplace due to factors such as temperature, abrasion and degradation etc. Further information on the maximum permissible user exposure, e.g. temperature, duration can be obtained from manufacturer

### Range Available: sizes and codes

Style	9	10
Vyflex 30cm	P93/09	P93/10
Vyflex BOA 35cm	PF94/09	PF94/10

### Antistatic properties

Vyflex and Vyflex BOA have been tested to EN 1149.

<b>EN1149-1</b>
<b>Surface Resistivity</b>
1.8 x 10 <sup>10</sup> Ω

Done at Enfield, 16/06/16

Bernard Garvey  
Technology Director