

EC-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (897686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° 0075/2003/162/12/17/1851

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment?

Manufacturer:

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

Distributor:

1

Description

PPE Type:

protective glove against mechanical risks

Product reference:

84302

Glove description:

13G Black Polyester with Black Nitrile Palm

This product is a category II.

Available sizes:

9/L 10/XL

Pictures:



Blackrock

84302 EN388

C € □ □

Size 10/XL 4.1.2.2.X

Reference standard:

Levels of performance / class of protection

EN 420:2003+A1:2009

EN 388:2016

4122X

The levels of performance have been measured on the palm

« X » means that the test hasn't been performed ; no protection is required

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from DECEMBER 2017

NOTA: Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Lionel Gaudillere
PPE certification manage

Date of issue: December 12th 2017



www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél.: ÷33 (0)4 72 76 10 10 - Fax : ±33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com



In application of the Directive 89/686/EEC of the 21th December 1989, concerning the alignment of member states legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

RODO LIMITED

MANUFACTURER'S TECHNICAL FILE

Reference of the product : 84302

Technical file index : 01

Last update : DECEMBER 2017

IDENTIFICATION

Reference of the product 84302

Basic model

Technical file index: 01

Last update DECEMBER 2017

Manufacturer:

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

tel: +44(0)01613716425 fax: +44(0)01613716465

GLOVE DESCRIPTION

Glove description:

13G Black Polyester with Black Nitrile Palm

type of coating finish: smooth

Visual description:



Field of use, Risks against which the product protects:

mechanical risk

Available sizes:

Minimum length of glove (mm)	Sizes	
250	9/L	
260	10/XL	

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		black	nitrile	250g/m2		0.5mm
		black	polyester	200g/m2	13	
Back		black	polyester	200g/m2	13	
Cuff		black	polyester/ elastic	250g/m2	13	
Binding		black/blue	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks. It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity:

5

PH of glove and lining is greater than 3.5 and lower than 9.5:

yes

Chromium VI lower than the detection limit:

conform

Size: conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388: 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	2
Cut Resistance method (EN ISO 13997)	X
Impact Protection	ž.

The levels of performance have been measured on the palm $\ll X$ » means that the test hasn't been performed; no protection is required

TEST REPORTS

Laboratory	стс	Other
EN 420	S151109732_1 SH60148-14	
Azo	S151109732_1 SH60148-14	
EN 388	S151109732_1 S161010569_1 S171114844_1 S171014321_1	
OTHER	S151109732_1(TIN CAD) S171014321_1 (PAHs) S170404669_1(DMFu)	

MARKING - PACKAGING

Information printed on the glove:

Logo of the authorized representative :

Logo (€

Glove's reference: 84302

Size indicator

Pictograms related to risks against which protection is offered with performance levels Information pictogram

Marking example:



Method of marking on the glove :

silk printing on the back of gloves

Packaging:

120PRS/DOZ,120PRS/CTN

MEANS OF CONTROL

1.Purchase Control According to quality influence degree of the final product in purchase, it is necessary to classify the purchased materials.

The main and large batch of products directly affecting the qualities of final products should be purchased in the name list of eligible sub-contractor. Except for the above, the other products could be purchased in the market directly.2.when all materials are set, the technician will check all the quality before mass products.3.Personal Control,After quality training, the project department organizes quality personnel, security personnel to understand the technical intentions, acceptance standard, quality aim and safety measures of the special process.4.Equipment control The project department is responsible for the inspection of the equipments used in the special process to ensure their perfection and make records.5.Packing control,when packing we have also QC to check goods, then keep all goods are qualitified

INSTRUCTION FOR USE

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

Glove reference: 84302

Available sizes 9/L 10/XL

Glove description:

13G Black Polyester with Black Nitrile Palm

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE: innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards:

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5 Moreover, this glove has been designed for the following applications :

Application : Mechanical hazard - EN 388



4 1 2 2 X Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	11	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		1

[«] X » means that the test hasn't been performed; no protection is required

Protection limit:

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.