

Notified body N° 0075

EC-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N°

0075/2003/162/11/15/1071

Is given to the following model of personal protective equipment :

Issued to:

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

Distributor:

1

Product reference:

54009

Description:

PPE Type:

Protective gloves against

mechanical risks.

Reference standard:

EN 388: 2003.


Category:

11

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the complete certificate N°0075/2003/162/11/15/1071.

Issued in Lyon by Lionel Gaudillere
Head of CE marking

Date of issue: November 02nd, 2015











In application of the Directive ref. 89/686/EEC of the 21st of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29th of July 1992 concerning the transposition of this Directive into French law,

CTC

4,rue Hermann Frenkel - 69367 Cedex 07 - France
Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr

authorized by decrees of the Ministry of Work, Employment and Health of the 20th of December 2010, registered under the number 0075, published in OJEC, delivers:

EC-TYPE EXAMINATION CERTIFICATE 0075/2003/162/11/15/1071

To the following model of personal protective equipment §

* reference of the model :

54009

* protective glove against

mechanical risks.

* Manufacturer :

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU UNITED KINGDOM

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status)

Drawn up in Lyon, on November 02nd, 2015

Issued by Lionel GALDILLERE

NOTA: Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information

should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.



1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index: 01

Reference: 54009 Basic Model

Dated: NOVEMBER, 2015

10G Yellow Brushed Acrylic, Palm Coated with Blue Latex Crinkle Dipping

Available sizes:

9 10 11

Visual description:



Material:

	Color	Material	Gauges	Thickness
PALM	blue	latex		
PALIVI	yellow	acrylic	10	
BACK	yellow	acrylic	10	
LINING				
CUFF	yellow	acrylic	10	
BINDING	black	polyester		



2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- * EN 420:2003+A1:2009
- General requirements for gloves and test methods

* EN 388:2003

- Protective glove against mechanical risks
- * At the date of certificate, the product is in compliance with Annex XVII of European REACh regulation (552/2009/EC and associated revisions)
- * This product is a category II.

References of test reports performed in order to verify the compliance with the requirements of the technical rules:

Laboratory	СТС	Other
EN 420	SH60148-14, S150403490	
Azo	SH60148-14, S150403490	
EN 388	S150403490	1
OTHER	S150403490 (DMFu, Tin, Cad)	

Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
2	2	4	2

The levels of performance have been measured on the palm



3. MARKING


Each glove is clearly marked with the following information:

- * Logo of the authorized representative:
- * **C** € marking
- * reference of the model:

54009

- * size
- * pictogram for mechanical risks followed by the performance levels
- * information pictogram

Marking example:



RODO LIMITED

MANUFACTURER'S TECHNICAL FILE

Reference of the product : 54009

Technical file index : 01

Last update : NOVEMBER, 2015

IDENTIFICATION

Reference of the product : 54009

Basic model

Technical file index: 01

Last update: NOVEMBER, 2015

Manufacturer:

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

tel: +44(0)01613716425 fax: +44(0)01613716465

GLOVE DESCRIPTION

Glove description:

10G Yellow Brushed Acrylic, Palm Coated with Blue Latex Crinkle Dipping

Visual description:



Available sizes :

Minimum length of glove (mm)	Sizes
250	9
260	10
270	11

Glove constitution:

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
PALM		blue	latex	500g/m2		
I ALIVI		yellow	acrylic	300g/m2	10	
BACK		yellow	acrylic	300g/m2	10	
LINING						
CUFF		yellow	acrylic	300g/m2	10	
BINDING		black	polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity: 5

PH of glove and lining is greater than 3.5 and lower than 9.5:

Chromium VI lower than the detection limit: conform

Size: conform

At the date of certificate, the product is in compliance with Annex XVII of European REACh regulation (552/2009/EC and associated revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388: 2003

Protection offered	Performance levels	
Abrasion resistance	2	
Blade cut resistance	2	
Tear strength resistance	4	
Puncture resistance	2	

The levels of performance have been measured on the palm

TEST REPORTS

Laboratory	СТС	Other
EN 420	SH60148-14, S150403490	
Azo	SH60148-14, S150403490	
EN 388	S150403490	
OTHER	S150403490 (DMFu, Tin, Cad)	

MARKING - PACKAGING

Information printed on the glove:

Logo of the authorized representative :

Logo (€


Glove's reference: 54009

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example:



Method of marking on the glove:

PRINT ON THE BACK OF GLOVES

Packaging:

1PR/HEAD CARD,12PRS/DOZ WITH USER INFORMATION SHEET,120PRS/CTN

MEANS OF CONTROL

1.Purchase Control According to quality influence degree of the final product in purchase, it is necessary to classify the purchased materials. The main and large batch of products directly affecting the qualities of final products should be purchased in the name list of eligible subcontractor. Except for the above, the other products could be purchased in the market directly.2.when all materials are set, the technician will check all the quality before mass products.3.Personal Control,After quality training, the project department organizes quality personnel, security personnel to understand the technical intentions, acceptance standard, quality aim and safety measures of the special process.4.Equipment control The project department is responsible for the inspection of the equipments used in the special process to ensure their perfection and make records.5.Packing control,when packing we have also QC to check goods, then keep all goods are qualitified

INSTRUCTION FOR USE

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

Glove reference: 54009

Available sizes: 9 10 11

Glove description:

10G Yellow Brushed Acrylic, Palm Coated with Blue Latex Crinkle Dipping

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE: innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (OO75) 4, rue Hermann Frenkel 69367 LYON Cedex 07 FRANCE

Applicable standards:

The glove meets the requirements of the standard EN 420 « General requirements for work glove », Dexterity : 5 Moreover, this glove has been designed for the following applications :



Application : Mechanical hazard - EN 388





2242 Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	2	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	2	(on 4 maxi)

Protection limit:

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entaglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.