



**PRODUCT NUMBER: NFD11HD**  
**Cold Grip Plus 5**

Handling in cold conditions of damp, oily or greasy parts with high cut risks. Ideally suited to tasks where workers need a combination of cold and cut protection, but don't want to give up comfort and dexterity.



**Overview**

**Reference Number**

NFD11HD

**Product Type**

Gloves

**Range**

Thermal Protection

**Line**

Cold

**Brand**

Honeywell

**Industry**

- Agriculture
- Building and Construction
- Catering
- Energy or Electricity
- Food Industries
- General Industry
- Green Spaces
- Logistics
- Maintenance
- Mining and Quarrying
- Offshore
- Ship Building
- Telecoms
- Wood Industries

**Product Use**

Handling in cold conditions of damp, oily or greasy parts with high cut risks. Ideally suited to tasks where workers need a combination of cold and cut protection, but don't want to give up comfort and dexterity.

## Features & Benefits

### Feature

Orange polyamide / composite fiber knitted glove  
 3/4 Black foam PVC HPT (Hydropellent technology™) coating Seamless  
 Brushed synthetic liner  
 Elastic knitted wrist

### Benefit

#### COMFORT

The ergonomic seamless knit construction conforms better to the natural shape of the hand for greater strength and durability, superior comfort.

Coating won't stiffen when cold, so glove retains its flexibility

#### RESISTANCE

The Polyamide yarn reduces linting for the most sensitive applications and can be easily laundered for extended use.

The foam PVC HPT is a soft, durable and flexible coating that repels liquids to provide a firm wet or dry grip. You need less pressure to handle an oily piece. It also provides an excellent abrasion resistance equal to heavier gloves. The 7 gauge brushed synthetic liner ensures superior insulation from the cold down to -20°C. HYGIENE The dark colors make the glove less dirty.

## Technical Description

### Description

CE CATEGORY: II Intermediary risks

In accordance with standards:

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical hazards

EN 511-2004 Cold hazards

#### CHARACTERISTICS:

Orange polyamide / composite fiber knitted glove  
 3/4 Black foam PVC HPT (Hydropellent technology™) coating Seamless  
 Brushed synthetic liner  
 Elastic knitted wrist

### Product Technology

Knitted dipped

### Fiber

Polyamide / composite fiber

### Gauge

15

### Glove/liner color

Orange

### Coating Type

PVC HPT

### Coating Color

black

### Length

25 cm

### Harmlessness

In conformity with the European standards

### Dexterity

Class 5

### Sizes

7S to 11XXL

## EN 388 - Mechanical Hazards Abrasion Resistance

|                                 |   |
|---------------------------------|---|
| Abrasion resistance             | 3 |
| Cutting resistance (Coupe test) | 5 |
| Tear resistance                 | 3 |

|                     |   |
|---------------------|---|
| Puncture resistance | 2 |
|---------------------|---|

## EN 511- Protection in cold temperatures:

|                               |   |
|-------------------------------|---|
| Resistance to conductive cold | 0 |
| Resistance to contact cold    | 2 |
| Water permeability            | 0 |

## Packaging Label

### Tagging

CE HONEYWELL  
NFD11HD XX  
EN 420  
EN 388: 3532  
EN 511: 020

## Certifications

### E.C. Declaration of Conformity

#### EC Category PPE

2

#### Quality Assurance

ISO 9001 / 2000

#### EC Certificate Number

0075/797/162/10/15/1008

#### EC Attestation

EC Attestation

#### EC Attestation Number

0075/797/162/10/15/1008

## Additional Information

### User Manual

UI 105

### User Information Sheet

105

## Maintenance

### Storage Information

Minimum packaging 12 pairs.  
Cartons of 72 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.



In application of the Directive ref. 89/686/EEC of the 21<sup>st</sup> of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29<sup>th</sup> of July 1992 concerning the transposition of this Directive into French law,

## CTC

4, rue Hermann Frenkel - 69367 Cedex 07 - France

Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupe.com - www.ctc.fr

Comité Professionnel de Développement Cuir Chaussure Maroquinerie - Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

authorized by decrees of the Ministry of Work, Employment and Health of the 20<sup>th</sup> of December 2010,

registered under the number 0075, published in OJEC, delivers :

### CE TYPE EXAMINATION CERTIFICATE 0075/797/162/10/15/1008

To the following model of personal protective equipment :

\* protective glove against mechanical risks, cold risks.

\* reference of the model : NFD11HD

\* responsible for placing on the market :

#### HONEYWELL SAFETY PRODUCTS EUROPE

Immeuble Edison ZI-Paris Nord II 33, Rue des Vanesses 95 958 ROISSY CDG CEDEX  
France

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on October 12th, 2015

Issued by Lionel GAUDILLERE



NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R. 4313-38 of the French Code of Work.

## 1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index : 01

Reference : NFD11HD

Basic Model

Dated : OCTOBER 2015

Glove composed of : gauge 15 polyamide an outer knitted lining for cold with 3/4 PVC coating and an insert of Terry lining.

### Available sizes :

6 7 8 9 10 11

### Visual description :



### Material :

|         | Colour | Material                                 | Gauges | Thickness |
|---------|--------|--|--------|-----------|
| PALM    | Orange | Polyamide/ High performance polyethylene | 13     |           |
|         | Black  | PVC                                      |        | 1,25mm    |
| BACK    | Orange | Polyamide/ High performance polyethylene | 13     |           |
| LINING  | Black  | Cotton, polyester, Polyamide, acrylic    | 10     |           |
| CUFF    | Orange | Polyamide/ High performance polyethylene | 13     |           |
|         | Black  | elastic rubber                           | 13     |           |
| BINDING | Black  | Polyester, elastane                      |        |           |

## 2. PROTECTION SCOPE

**Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:**

- \* EN 420:2003+A1:2009 - General requirements for gloves and test methods
- \* EN 388:2003 - Protective glove against mechanical risks
- \* EN 511 : 2006 - Protective gloves against cold
- \* At the date of certificate, the product is in compliance with Annex XVII of European REACH regulation (552/2009/EC and associated revisions)

**References of test reports performed in order to verify the compliance with the requirements of the technical rules :**

| Laboratory | CTC Asia | CTC France                                   | Other |
|------------|----------|--|-------|
| EN 420     |          | L150812711_1<br>L150913739_1                 |       |
| Azo        |          | L150812711_1                                 |       |
| EN 388     |          | L150812776_1<br>L150913739_1<br>L150914661_1 |       |
| EN 511     |          | L150913739_1<br>L150812801_1                 |       |

**Performance levels offered against mechanical risks (EN 388:2003) are:**

| Abrasion resistance | Blade cut resistance | Tear strength resistance | Puncture resistance |
|---------------------|----------------------|--------------------------|---------------------|
| 3                   | 5                    | 3                        | 2                   |

The levels of performance have been measured on the palm

**Performance levels offered against cold (EN 511:2006) are:**

| Convective cold | Contact cold | Water penetration |
|-----------------|--------------|-------------------|
| 0               | 2            | 0                 |

### 3. MARKING

**Each glove is clearly marked with the following information:**

- \* Logo of the authorized representative:
- \* **CE** marking
- \* reference of the model: NFD11HD
- \* size
- \* pictogram for mechanical risks followed by the performance levels
- \* pictogram for cold risks followed by the performance levels
- \* information pictogram

**Marking example:**





# E.C. Declaration of Conformity

**The manufacturer or its legal representative supplier in the European Community:**

Honeywell Safety Products Europe

**Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:**

Designation: Cold Grip Plus 5

Reference: NFD11HD

Standard(s): EN 388, EN 420, EN 511

**This PPE is the object of the below EC examination certificate n°:**

0075/797/162/10/15/1008

**Delivered by:**

CENTRE TECHNIQUE DU CUIR

4 rue Hermann Frenkel

69367 LYON Cedex 07

France

Drawn up in Lyon, on the 19/09/2018

**By:** Fabrice Beaugeard

**Division:** Gloves

HONEYWELL SAFETY PRODUCTS EUROPE  
Immeuble Edison - ZI Paris Nord II - 33 rue des Vanesses  
BP 55288 Villepinte - 95988 ROISSY CDG CEDEX  
SAS au capital de 200 000 € - N° SIRET 3331 4990 7980  
Tel: +33 1 49 90 79 79 - Fax: +33 1 49 90 79 80

ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

[www.honeywellsafety.com](http://www.honeywellsafety.com)