

NITRILE JUBA - H1118HV REFLECTOR

High visibility Polyester and Spandex liner with nitrile foam palm coating.



NORMATIVE



EN 388:2016+A1:2018



3121X



CHARACTERISTICS

- Its fluor liner enhances the visibility of the hands in dark environments.
- Nitrile foam provides protection against oil and fats while offers flexibility and dexterity.
- Good grip on oily, wet and dry surfaces.
- Very thin seamless liner in gauge 15 for greater flexibility, touch and comfort.
- Touchscreen capabilities.

WORKING GLOVES SUITABLE FOR:

- Construction and masonry.
- Gardening.
- Maintenance and civil Works.
- Cleaning and public services.
- Waste collection.
- Mechanical workshops.

MORE INFO

Materials	Colour	Thickness	Length	Sizes	Packaging
Nitrile	Fluorescent Yellow / Black	Gauge 15	XS - 22 cm S - 23 cm M - 24 cm L - 25 cm XL - 26 cm XXL - 27 cm	6/XS 7/S 8/M 9/L 10/XL 11/XXL	10 pairs/package 120 pairs/box

NORMATIVES


EN388:2016



EN388:2016 Protective gloves against mechanical risks.

The EN388: 2003 standard is renamed EN388: 2016, the year of its revision. The reason for the modification is given by the discrepancies in the results between laboratories in the knife cut test, COUP TEST. Materials with high levels of cut produce a dulling effect on the circular blades, which undermines the result.

The new regulation was published in November 2016 and the previous one is from the year 2003. During these 13 years, there has been a great innovation in the materials for the manufacture of cutting gloves, they have forced to introduce changes in the tests to be able to measure with more rigorous levels of protection.



- A - Abrasion resistance (X, 0, 1, 2, 3, 4)
- B - Blade Cut Resistance (X, 0, 1, 2, 3, 4, 5)
- C - Tear resistance (X, 0, 1, 2, 3, 4)
- D - Puncture resistance (X, 0, 1, 2, 3, 4)
- E - Cutting by sharp objects ISO 13997 (A, B, C, D, E, F)
- F - Impact test complies / does not comply (It is optional. If it complies, put P)

En388:2016 performance levels

	1	2	3	4	5
6.1 abrasion resistance (cycles)	100	500	2000	8000	-
6.2 blade cut resistance (index)	1,2	2,5	5	10	20
6.4 tear resistance (newtons)	10	25	50	75	-
6.5 puncture resistance (newtons)	20	60	100	150	-

Eniso13997:1999 performance levels

	A	B	C	D	E	F
6.3 tdm: cut resistance (newtons)	2	5	10	15	22	30