

Information User instruction

Safety gloves against chemical and mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg GERMANY

Type uvex profastrong - NF33 Basic glove material flocked cotton Available sizes 7, 8, 9, 10

Tel.: +49 4131 9502-0 Fax: +49 4131 84338 Email: gloves@uvex.de Website: uvex-safety.de

Coating material Smallest packing unit NBR (nitrile butadiene rubber) 144 Pairs

Pictogram and performance levels EN 374 : 2003




AJKL

Performance level

min)

min)

| Methanol | Class 2 (> 30 min) |
|----------------------|--------------------|
| n-heptane | Class 6 (> 480 min |
| Sodium hydroxide 40% | Class 6 (> 480 min |
| Sulphuric acid 96% | Class 3 (> 60 min) |



Pictogram and performance levels according to EN 374:2003 (lowest performance level: 1/highest performance: 6)

The sampling for penetration testing is made by general inspection level according to DIN 2859, part 1 with AQL 4.0.

Please note: The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

| Warning | Gloves should not be worn where there is a risk of being caught in moving machinery parts. |
|------------------|--|
| Disposal | The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines. |
| | After contamination, a change of performance cannot be excluded. We are not aware of any substances in this product that could cause an allergic reaction. |
| Handling | Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374). Gloves must be disposed of when the permeation time expires. |
| Storage | Store in a dark, dry place. |
| Cleaning | Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under lukewarm running water. |
| EC notified body | SGS United Kingdom Ltd., Systems & Services Certification 202 B Worle Parkway · BS22 6WA Weston-Super-Mare, United Kingdom No.: 0120 |
| | |

protecting people